



SEROLOGICAL WATER BATH

(DOUBLE WALL)

Double walled construction with outer body made of mild steel painted with white powder coating paint. Inner chamber made of S/Steel sheet perforated bottom tray & pyramidal lid made of Stainless Steel. Insulation is done by High Grade Glass Wool in between the walls Gap. A drain plug made of Brass is provided at the bottom of chamber.



Temp. Range : Temperature inside the chamber is controlled by Capillary Thermostat from ambient to 80°C with an accuracy of +/-0.5°C.

Indicator : A 'L' shaped Prismatic thermometer is given to indicate temperature.

Heating : Heating effects are created by heating element (ISI Marked) placed at the bottom of the inner chamber.

S.No. Available Size (L × B × H)

- a) 300 × 250 × 150 mm (for 2 racks)
- b) 325 × 300 × 150 mm (for 4 racks)
- c) 450 × 300 × 150 mm (for 6 racks)
- d) 600 × 300 × 150 mm (for 8 racks)

Optional Accessories :

1. Stirrer with 1/20 HP high speed motor with S/Steel stirring rod & blade provided with speed regulator.
 2. Digital temperature controller cum indicator with stirrer.
- Complete with cord not panel showing Indicators & switches and Instruction Manual. To work on 220/230 Volts, AC 50 Hz., Single Phase.

WATER BATH RECTANGULAR

(DOUBLE WALL)



Water Bath Rectangular (Double Wall) : Outer body made of mild steel painted with white stoving enamel. Inner chamber made of thick S/Steel complete with concentric rings. Temperature controlled by hydraulic thermostat from ambient to 95°C, +/- 1°C. Complete with control panel but without Thermometer. To work on 220/230VAC.

S.No. Available Size (L × B × H)

- a) 300 × 250 × 100 mm (6 holes 75mm dia)
- b) 330 × 300 × 100 mm (9 holes 75mm dia)
- c) 425 × 325 × 100 mm (12 holes 75mm dia)

Optional Accessories :

1. Stirrer with 1/20 HP high speed motor with S/Steel stirring rod & blade provided with speed regulator.
2. Digital temperature controller cum indicator with stirrer.